

ANTISLIP AGENT

PRODUCT DESCRIPTION:

Polypropylene granulate ensuring a slip-resistant surface in combination with Arturo Sealers Arturo EP7610, PU3320, PU7180, PU7310, PU7320, PU7750

AREA OF APPLICATION***

Arturo antislip agents are suitable to be processed in the following Arturo Sealers:

- ▶ Arturo EP7610 Sealer (2-C, EP, matt, transparent)*
- ▶ Arturo PU7180 Sealer (1-C, PU, gloss, transparent)*
- ▶ Arturo PU7750 Sealer (2-C, PU, dull matt, transparent)*
- ▶ Arturo PU7320 Sealer (2-C, PU, satin, transparent)*
- ▶ Arturo PU3320 Sealer (2-C, PU, satin, coloured)*

PRODUCT FEATURES/BENEFITS

- ▶ Available in different gradations
- ▶ White colour
- ▶ Polypropylene



PRODUCT DATA

Packaging size	Art# 35622 AS agent, bucket 0,1375 kg for: Arturo PU7180 Sealer Arturo PU7750 Sealer Arturo EP7610 Sealer
	Art# 79617 AS agent, bucket 0,165 kg for: Arturo PU3320 Sealer Arturo PU7320 Sealer
Shelf life	12 months
Colour	White
Grain size (average)	AS agent: 210 µm

TECHNICAL SPECIFICATIONS:

Frost resistance	Yes
------------------	-----

DISCLAIMER

The information on this product sheet concerning the processing and application of this product is based on our experience with the product under standard conditions and with correct product storage and use. In practice, differences between equipment, subfloors and working conditions mean that no guarantee for a specific work result nor any liability, arising out of any legal relationship whatsoever, can be inferred either from the information on this data sheet or from any verbal advice given, unless caused by intent or gross negligence on our part. In this case the user must demonstrate that he has promptly forwarded to us in writing all necessary information for proper and effective evaluation of the circumstances. Users must test the products to check whether they are suitable for the intended application. We reserve the right to amend the information on technical data sheets. The intellectual property rights of third parties must be heeded. The most recent technical data sheet always applies. This can be requested from us or downloaded from www.arturoflooring.com. Our general terms and conditions of sale and delivery also apply.

PROTECTION OF THE WORKPLACE AND ENVIRONMENT:

The use of barrier cream is recommended. When mixing wear a protective dust-mask. Refer to the notes on protection of the workplace and the environment in the Product Information Sheets for the other installation materials used.

DISPOSAL:

Where possible, collect product residues and re-use. Do not empty into drains, sewers or ground. Empty, scraped containers are recyclable.

* At 20°C, 65% relative humidity.

** Avoid large temperature fluctuations and differences, this can lead to a temperature shock which has a negative influence on the final result.

*** For recreation rooms systems with AgBB certification must be used.