

ARTURO BALLOTINI

PRODUCT DESCRIPTION:

Solid glass spheres ensuring a slip-resistant surface in combination with Arturo Sealers, different sizes

AREA OF APPLICATION***

Arturo Ballotini are suitable to use in:

- ▶ Arturo Floor Coatings
- ▶ Arturo Sealers

PRODUCT FEATURES/BENEFITS

- ▶ Transparent
- ▶ Solid glass beads
- ▶ 3 different sizes
- ▶ Non-flammable
- ▶ High abrasion resistance



PRODUCT DATA

Packaging size	Bag: 25 kg
Shelf life	12 months
Colour	Transparant
Grain size (average)	75 - 150 µm
	180 - 300 µm
	250 - 425 µm

TECHNICAL SPECIFICATIONS:

Mixing ratio	See 'Slip resistance overview' to determine the right amount of Arturo Ballotini
Frost resistance	Yes

APPLICATION:

Stir component A thoroughly. Add component B and immediately mix for at least 2 minutes with an electrical mixer (speed ca. 300 – 400 rpm). Then add the supplied anti-slip particles and mix thoroughly again with a mixer that is also able to mix the material at the bottom of the container (mixing time ca. 2 minutes). Then transfer all the mixture to a clean container. For processing we recommend using a bucket with wipe-off grid.

The processing procedure is the same as for applying the sealant without anti-slip particles.

After 16-24 hours apply the second layer in exactly the same way as the first layer, but without addition of anti-slip particles.

Attention: Arturo Balltoni tend to sink to the bottom. Therefore, mix the material frequently to keep it homegeneous.

DISCLAIMER

The information on this product sheet concerning the processing and application of this product is based on our experience with the product under standard conditions and with correct product storage and use. In practice, differences between equipment, subfloors and working conditions mean that no guarantee for a specific work result nor any liability, arising out of any legal relationship whatsoever, can be inferred either from the information on this data sheet or from any verbal advice given, unless caused by intent or gross negligence on our part. In this case the user must demonstrate that he has promptly forwarded to us in writing all necessary information for proper and effective evaluation of the circumstances. Users must test the products to check whether they are suitable for the intended application. We reserve the right to amend the information on technical data sheets. The intellectual property rights of third parties must be heeded. The most recent technical data sheet always applies. This can be requested from us or downloaded from www.arturoflooring.com. Our general terms and conditions of sale and delivery also apply.

PROTECTION OF THE WORKPLACE AND ENVIRONMENT:

No special measures are required. Refer to the notes on protection of the workplace and the environment in the Product Information Sheets for the other installation materials used.

DISPOSAL:

All product residues are treated as normal construction waste.

* At 20°C, 65% relative humidity.

** Avoid large temperature fluctuations and differences, this can lead to a temperature shock which has a negative influence on the final result.

*** For recreation rooms systems with AgBB certification must be used.