

ARTURO FLAKES

PRODUCT DESCRIPTION:

Colour flakes for a creative floor design, lightly or fully scattered onto the fresh top layer, large variety of colours, many standard mixtures, different sizes

AREA OF APPLICATION***

Arturo Flakes can be strewn to create a gradual build-up of colour or fully gritted to ultimately mask the floors base colour entirely. Arturo Flake colours can be combined to create a unique effect. Arturo Flakes are strewn onto wet coatings or Self-smoothing Floors and then finished using one or more Top Coats.

PRODUCT FEATURES/BENEFITS

- ▶ Available in many colours, see 'flakes colour overview'
- ▶ Available in 3 different gradations



PRODUCT DATA

Packaging size	Available per kg in 2 sizes
Shelf life	12 months

DISCLAIMER

The information on this product sheet concerning the processing and application of this product is based on our experience with the product under standard conditions and with correct product storage and use. In practice, differences between equipment, subfloors and working conditions mean that no guarantee for a specific work result nor any liability, arising out of any legal relationship whatsoever, can be inferred either from the information on this data sheet or from any verbal advice given, unless caused by intent or gross negligence on our part. In this case the user must demonstrate that he has promptly forwarded to us in writing all necessary information for proper and effective evaluation of the circumstances. Users must test the products to check whether they are suitable for the intended application. We reserve the right to amend the information on technical data sheets. The intellectual property rights of third parties must be heeded. The most recent technical data sheet always applies. This can be requested from us or downloaded from www.arturoflooring.com. Our general terms and conditions of sale and delivery also apply.

PROTECTION OF THE WORKPLACE AND ENVIRONMENT:

The use of barrier cream is recommended. When mixing wear a protective dust-mask. Refer to the notes on protection of the workplace and the environment in the Product Information Sheets for the other installation materials used.

DISPOSAL:

Where possible, collect product residues and re-use. Do not empty into drains, sewers or ground. Empty, scraped containers are recyclable.

* At 20°C, 65% relative humidity.

** Avoid large temperature fluctuations and differences, this can lead to a temperature shock which has a negative influence on the final result.

*** For recreation rooms systems with AgBB certification must be used.