

FLOOR GUIDE

	Systems:	Arturo EP1000 / EP1200 / EP1250 mortar floors	Arturo PU2030 self-smoothing floor	Arturo PU2060 self-smoothing floor	Arturo EP2400 self-smoothing floor (conducting)	Arturo EP2500 self-smoothing floor	Arturo EP3600 floor coating	Arturo EP3900 floor coating (coloured)	Arturo OS 8 (DA&StB-OS8)	Arturo flame design self-smoothing floor
	Load:									
1	Light		X				X	X		X
2	Light to medium (asphalt)			X			X			X
3	Light to medium (open to diffusion)						X			
4	Medium			X		X		X		X
5	Medium, smooth			X	X	X	X	X		X
6	Medium, rough					X		X	X	
7	Medium to heavy	X				X				X
8	Medium to heavy, smooth	X				X				X
9	Medium to heavy, rough	X				X				
10	Conducting < 10.6 ohms				X					

Uzin Utz Nederland bv operates the quality assurance system in accordance with NEN-EN ISO-9001/14001 and is certified for this by TÜV Nederland QA. This means that deliveries are made in accordance with the product and process specifications drawn up for this system. Products and services supplied by Uzin Utz Nederland bv also comply with the description in these technical specifications. As different site conditions and working practices are unknown, Uzin Utz Nederland bv accepts no liability for any damage resulting from any use of its products. With the publication of this data sheet, all previously published data sheets concerning this product become invalid. © Uzin Utz Nederland bv. All rights reserved. Copying and/or reproduction of this publication, in whatever form, is not permitted without the written permission of Uzin Utz Nederland bv. | 03.2020