

CE

DoP DECLARATION OF PERFORMANCE 2035-2017.07.10-04

according to Regulation (EU) No 305/2011 Annex III (Construction Products Regulation)

For the product:

UZIN PAST 100

Reference No:

(equal for DoP and CE marking)

1. Unique identification code of the product-type:

UZIN PAST 100 EN 998-2:2010 2035-20170710-04

Article No-Date of first update-certificate No

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Lot-Number: see packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

General purpose rendering mortar (GP) for external renovation use (R)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

UZIN Hellas POLYCHIMIKI G. MATZIARIS S.A.

14th Km Old National Rd Thessaloniki - Veria

Industrial Park of Anchialos,

GR 570 11 Thessaloniki - Greece

Tel. +30 2310 722991-3

Fax +30 2310 722571

e-mail: uzin@otenet.gr, info@uzin.gr

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

The notified body, identification number [0761], performed the determination of the class regarding reaction to fire on the basis of product testing under system 3 and issued the following classification report:
K-3128/233/12-MPA BS

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance:

*NPD= No performance determined

	Essential characteristics	Performance	Normative references	Harmonised technical specification
1	Dry bulk density	1280 kg/m ³	EN 1015-10	EN 998-2:2010
2	Compressive strength	Κατηγορία M2,5	EN 1015-11	
3	Bond strength	≥ 0,15 N/mm ²	EN 1052-3	
4	Water absorption	12,1 %	EN 1015-18	
5	Air content	5,1 %	EN 1015-7	
6	Chloride content	≤ 0,1 %	EN 1015-17	
7	Working time	> 150 min	EN 1015-9	
8	Durability(freeze/thaw)	NPD		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Dr. Katia Matziaris, B.Sc.Geo., D.Che.E.
Quality & Safety Compliance Manager

(name and position)

POLYCHIMIKI
G. MATZIARIS S.A.

POLYCHIMIKI - G. MATZIARIS S
 14thkm Old National Road of Thessalonikj - V
 Industrial Park Of Anchialos GR 57011 Thessalc
 P.O. Box 1073 GR 57022 - SINDOS GREECE
 TEL. +30 2310 722 991 - 2 FAX: +30 2310 722
 VAT No: EL 094411058 - e-mail: uzin@oten

Thessaloniki, 18/03/2025

(place and date of issue)

(stamp)

(signature)

*NPD= No performance determined