

CE

DoP DECLARATION OF PERFORMANCE

according to Regulation (EU) No 305/2011 Annex III (Construction Products Regulation)

For the product by trade name:

UZIN POLYTOL HYBRID

Reference No:

(equal for DoP and CE marking)

1. Unique identification code of the product-type:

UZIN POLYTOL HYBRID 2291-2017.07.10-07

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Lot-Number: see packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

EN 1504-2:2004

Surface protection products hydrophobic impregnation:

1 - Protection against Ingress (PI) &

2 - Moisture Control (MC)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

UZIN Hellas POLYCHIMIKI G. MATZIARIS S.A.

14th Km Old National Rd Thessaloniki - Veria

Industrial Park of Anchialos,

GR 570 11 Thessaloniki – Greece

Tel. +30 2310 722991-3

Fax +30 2310 722571

e-mail: uzin@otenet.gr, info@uzin.gr

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

The notified body, identification number [0761], performed the determination of the class regarding reaction to fire on the basis of product testing under system 3 and issued the following classification report:
K-3128/233/12-MPA BS

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

*NPD= No performance determined

Not relevant

9. Declared performance:

	Essential characteristics	Performance	Normative references	Harmonised technical specification
1	Permeability to CO ₂	S _D > 50 m	EN 1062-6	EN 1504-2
2	Permeability to water vapor	Class III S _D > 50 m	EN ISO 7783-1 & 2	
3	Capillary absorption and permeability to water	w < 0,1 kg/(m ² h ^{0.5})	EN 1062-3	
4	Adhesion strength by pull-off test	≥ 0,8 N/mm ²	EN 1542	
5	Resistance to severe chemical attack	Petroleum: Class I Acetic acid 20%: Class II Sodium Hydroxide 20%: Class II Hydrochloric acid: Class II	EN 13529	
6	Artificial weathering	NPD		
7	Reaction to fire	NPD		
	Dangerous substances comply with 5.4	Does not contain		

10. The performance of the product identified in points 9.4.5-9.4.7 in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dr. Katia Matziaris, B.Sc. Geo., D.Che.E.
Quality & Safety Compliance Manager

(name and position)

POLYCHIMIKI
G. MATZIARIS S.A.

POLYCHIMIKI - G. MATZIARIS S.
 14th km Old National Road of Thessalonikj - V
 Industrial Park Of Anchialos GR 57011 Thessalok
 P.O. Box 1073 GR 57022 - SINDOS GREECE
 TEL. +30 2310 722 991 - 2 FAX: +30 2310 722
 VAT No: EL 094411058 - e-mail: uzin@otenet.gr

Thessaloniki, 20/03/2025

(place and date of issue)

(stamp)

(signature)

*NPD - No Performance Determined

*NPD= No performance determined