

Care emulsion for ECO OIL treated wood floors

ECO OIL CARE

Water-based care emulsion for initial and maintenance care on oiled wood floors, treated with ECO OIL 1K. Also suitable for layer-forming wood floor oils.

PRODUCT DESCRIPTION:

Water-based care emulsion that, by means of a dirt-repellent protective film, improves the seal and appearance of the surface and at the same time extends the wear life of the flooring.

AREA OF APPLICATION:

Care product for maintenance-cleaning of oiled wood floors treated with PALLMANN ECO OIL 1K or PALLMANN HARDWAXOIL.



PRODUCT BENEFITS / PROPERTIES:

- ▶ fast drying
- ▶ hard wearing
- ▶ no polishing required

TECHNICAL DATA:

Packaging:	plastic container
Packsize:	0,75 and 5 l
Consumption:	Initial care: approx. 20 - 30 ml/m ² Maintenance care: approx. 250 ml/5 l water
Working climate:	between 18 – 25 °C and 35 – 65 % relative humidity

SURFACE PREPARATION:

Remove traces of dirt and dust by using the PALLMANN MOP, broom or vacuum cleaner.

APPLICATION:

1. Before use, the container must be brought to room temperature (20 °C) and must be shaken well.
2. **Initial care:** Apply a thin, even coat of PALLMANN ECO OIL CARE using a PALLMANN FLOOR MOP. Apply undiluted product at a rate of 20 -30 ml per square metre. No buffing is required.
3. **Maintenance care:** Carry out routine cleaning with PALLMANN CLEAN. Afterwards dilute approx. 250 ml PALLMANN ECO OIL CARE with 5 litres of water. When the flooring appears grey increase the dosage up to undiluted application. Apply evenly in one direction using the damp (not wet) PALLMANN MOP and let it dry. The maintenance care should be carried out as required.
4. After drying (approx. 1 hours) the surface can be put back into use.
5. After use, clean tools with water.
6. The exact maintenance and care routine is shown in the respective care instruction.

IMPORTANT NOTES:

- ▶ Optimum temperature is 18 to 25 °C with the relative humidity > 35 % and < 65 %. Low temperatures and high humidity will extend the drying time. High temperatures and low humidity will shorten the drying time.
- ▶ Shelf life minimum 24 months in original packaging when stored in dry conditions. Protect from freezing and do not expose to temperatures over 40 °C.
- ▶ Tightly reseal opened containers.
- ▶ When using our care products, especially on factory finished floors, and in rare cases there may be some appearance differences. We therefore recommend to create a small sample area in advance to check compatibility.
- ▶ Leave freshly oiled surfaces until fully hardened before treating with PALLMANN ECO OIL CARE.
- ▶ Flecks and applicator marks can be removed with PALLMANN CLEAN on a cloth or non-scratch PALLMANN CLEANING PAD WHITE.
- ▶ Regular maintenance with PALLMANN ECO OIL CARE improves the appearance and increases the wear life of the oiled surface. Only damp (not wet). Avoid standing water.
- ▶ The following standards and notices are applicable and especially recommended: DIN 18356 "Working with parquet and woodblocks", DIN 18365 "Working with floor coverings":

PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

Not flammable. Use of barrier cream and ventilation of the work area are recommended.

DISPOSAL:

Do not allow dispersal into drains, sewers or ground. Rinse containers, which have been emptied from any residues, with little water and dispose of the containers in accordance with local guidelines as recyclable packaging. Collect and reuse rinsing water and product remnants. If even necessary, dispose of containers with residues as well as product remnants as special waste.