



PALLMANN®

FOR WOOD FLOORS. FOR LIFE.

OBJECT-RELATED CARE INSTRUCTION

**FOR WOOD FLOORS OILED WITH PALLMANN
MAGIC OIL PRODUCTS**

**CREATED YOUR WOOD FLOOR IN THE
CONSTRUCTION PROJECT**

Dear

Object name

Your wood floor maintenance contractor

Street, number

Postcode, city

EXPERTLY AND ACCORDING TO CRAFTSMAN RULES.

LIZIN UTZ®

CARE INSTRUCTION

FOR WOOD FLOORS OILED WITH MAGIC OIL PRODUCTS



General notes:

Oiled wood floors may only be walked on, maintained or covered with carpets after complete drying of the surface.

Product	Drying	Care product	Cleaning product
MAGIC OIL 2K ORIGINAL	12 hours	MAGIC OIL CARE	CLEAN
MAGIC OIL 2K ERGO	12 hours	MAGIC OIL CARE	CLEAN
MAGIC OIL 2K SPA	12 hours	MAGIC OIL CARE	CLEAN
MAGIC OIL 2K CHANGE	12 hours	MAGIC OIL CARE	CLEAN
MAGIC OIL 2K WHITE	24 hours	MAGIC OIL CARE WHITE	CLEAN
MAGIC OIL 2K PURE	24 hours	MAGIC OIL CARE WHITE	CLEAN
MAGIC OIL 1K EASY	4-7 days	MAGIC OIL CARE	CLEAN
MAGIC OIL 1K CHANGE	7 days	MAGIC OIL CARE	CLEAN
PALL-X 333 COLOR WHITE*	24 hours	MAGIC OIL CARE WHITE	CLEAN
PALL-X 333 SOBER WHITE*	24 hours	MAGIC OIL CARE WHITE	CLEAN

* in combination with MAGIC OIL 2K ORIGINAL or MAGIC OIL 2K ERGO

table 1

THE WOODEN FLOOR IN THE PROPERTY MENTIONED OVERLEAF IS TO BE MAINTAINED AS FOLLOWS:

MAGIC OIL CARE
MAGIC OIL CARE WHITE

1. MAINTENANCE CLEANING WITH PALLMANN CLEAN

Processing:

1. Remove traces of dirt and dust by using a **PALLMANN MOP**, broom or vacuum cleaner.
2. Shake container well before use.
3. Dilute approximately 50 - 100 ml **PALLMANN CLEAN** in 5 l water.
4. Apply a thin, even coat using the **PALLMANN MOP**.
5. The maintenance cleaning depends on the degree of soiling and desired hygiene.

2. MAINTENANCE CARE WITH PALLMANN MAGIC OIL CARE (WHITE)

PALLMANN MAGIC OIL CARE protects the oiled floor through its regreasing effect and provides slip resistance. The properties of the maintained surfaces are preserved. **PALLMANN MAGIC OIL CARE WHITE** is suitable for the surface care of all common white pigmented (see table 1) oiled wood floors.

Processing:

1. Carry out maintenance cleaning with **PALLMANN CLEAN**.
2. Shake container well before use.
3. Maintenance care: Dilute approximately 250 ml **PALLMANN MAGIC OIL CARE (WHITE)** in 5 l water. In case of heavy graying increase the concentration (possibly up to the pure application).
4. Apply an even coat in direction of the wood fibre using the **PALLMANN MOP** and let it dry.
5. Clean tools with water after use
6. The maintenance cleaning depends on the degree of soiling

To maintain the dirt-repellent care, the maintenance care must be repeated in the object mentioned overleaf at the following intervals:

once a week
twice a week
three times a week
daily

CARE INSTRUCTION

FOR WOOD FLOORS OILED WITH MAGIC OIL PRODUCTS



3. DEEP CLEANING WITH PALLMANN CLEAN

Prepares the floor for renewed maintenance with the **PALLMANN MAGIC OIL series**. The renewed care prolongs the life of waxed and oiled floors.

Processing:

1. Remove traces of dirt and dust by using a **PALLMANN MOP**, broom or vacuum cleaner.
2. Shake container well before use.
3. Dilute approximately 200 ml **PALLMANN CLEAN** in 5 l water.
4. With a brush once damp (not wet) or clean the floor mechanically with a polishing machine and a green pad
5. Wipe with clean water and remove any dirt. Please work as dry as possible. An over-concentration of **PALLMANN CLEAN** leads to increased surface smoothness.
6. Clean tools with water after use.
7. The number of cleanings depends on the degree of soiling.

After deep cleaning, the floor must be re-oiled with the appropriate product.

Maintenance must be carried out as soon as parts of the surface appear dull or the first traces of wear are visible on the surface. In the above-mentioned object, we recommend carrying out aftercare:

monthly
quarterly
half-yearly

To avoid spontaneous combustion:

Materials soaked with PALLMANN MAGIC OIL products (especially rags and other textile materials) must be watered after use or stored in airtight sheet metal containers!

A healthy indoor climate serves the well-being of people as well as maintaining the value of your wood floor. Wood is a natural material that adapts to the humidity of the air by absorbing moisture from the air or releasing moisture into the air. Changes in humidity cause the wood to swell or shrink, which can result in **element compression** or **gaps** in the wooden floor. For this reason, we recommend a room temperature of 18 °C to 20 °C with a relative humidity of 50 % - 60 %. A hygrometer is a valuable aid for measuring and controlling the room climate. Room humidifiers can help to optimise room humidity, especially during the winter period. Oils generally tend to turn dark yellow when exposed to light, especially white pigmented oil systems. PALLMANN, as the manufacturer, does not assume any guarantee for the work carried out.

Attention:

Castors and glides must comply with EN 12529 (plastic or felt). We recommend a suitable floor protection mat under swivel chairs. Metal furniture and objects require a protective mat. Never use steel wool or other rough cleaning agents. Do not place any materials containing softeners, e.g. rubber or caoutchouc, directly on the wood floor. Furthermore, the use of adhesive tapes on the finished wood floor can lead to detachment of the surface layer, residues and / or discolouration. Materials containing plasticisers such as carpet underlays, furniture feet, tyres and chair castors can lead to discolouration of the floor. (Animal) faeces must be removed from the wood floor immediately to avoid surface irritation. In the entrance area, a sufficiently dimensioned dirt trap zone must be installed and taken into account!

Wood floor layer (signature) was confirmed

Customer (signature)

Your wood floor maintenance contractor

Date