

UZIN F-85 - Adhesive for printing benches



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: UZIN F-85 - Adhesive for printing benches

Other means of identification:

UFI: 6AW2-Q0D1-400K-QSXW

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses (Professional users): Adhesive

Relevant uses (Industrial user): Adhesive

For Professional users/Industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

POLYCHIMIKI G. MATZIARIS S.A.

14th Km Old National Rd Thessaloniki-Anchialos, Industrial Park of Anchialos

POBox 1073, GR-57022 SINDOS Thessaloniki - Greece

Phone: +302310722991-2 - Fax: +302310722571

uzin@otenet.gr

www.uzin.gr

1.4 Emergency telephone number: +30 210 7793777 National Poison Center

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Skin Sens. 1: Sensitisation, skin, Category 1, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P261: Avoid breathing vapours

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P302+P352: IF ON SKIN: Wash with plenty of water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment

Supplementary information:

Contains Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1).

Substances that contribute to the classification

Rosin (CAS: 8050-09-7)

UFI: 6AW2-Q0D1-400K-QSXW

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

UZIN F-85 - Adhesive for printing benches



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

3.1 Substance:

Not relevant

3.2 Mixture:

Chemical description: Mixture composed of resins in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification | Chemical name/Classification | Concentration |
|--|---|--------------------------|
| CAS: 8050-09-7 EC: 232-475-7 Index: 650-015-00-7 REACH: 01-2119480418-32-XXXX | Rosin⁽¹⁾ Regulation 1272/2008 Skin Sens. 1: H317 - Warning | ATP CLP00 2,5 - <10 % |
| CAS: 108-88-3 EC: 203-625-9 Index: 601-021-00-3 REACH: 01-2119471310-51-XXXX | Toluene⁽¹⁾ Regulation 1272/2008 Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger | ATP CLP00 1 - <2,5 % |
| CAS: 108-38-3 EC: 203-576-3 Index: 601-022-00-9 REACH: 01-2119484621-37-XXXX | m-xylene⁽²⁾ Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning | ATP CLP00 <1 % |
| CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX | N-butyl acetate⁽²⁾ Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning | ATP CLP00 <1 % |
| CAS: 55965-84-9 EC: Not relevant Index: 613-167-00-5 REACH: Not relevant | Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)⁽¹⁾ Regulation 1272/2008 Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger | ATP ATP13 <1 % |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

| Identification | M-factor | |
|----------------|---|-------|
| | Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Not relevant | Acute |
| | Chronic | 100 |

| Identification | Specific concentration limit |
|--|--|
| Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Not relevant | % (w/w) >=0,6: Skin Corr. 1C - H314 0,06<= % (w/w) <0,6: Skin Irrit. 2 - H315 % (w/w) >=0,6: Eye Dam. 1 - H318 0,06<= % (w/w) <0,6: Eye Irrit. 2 - H319 % (w/w) >=0,0015: Skin Sens. 1A - H317 |

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

| Identification | Acute toxicity | Genus |
|--|--|---------------|
| Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Not relevant | LD50 oral 64 mg/kg LD50 dermal 87,12 mg/kg LC50 inhalation vapour 0,5 mg/L | Rat Rabbit |

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

- CONTINUED ON NEXT PAGE -

UZIN F-85 - Adhesive for printing benches



SECTION 4: FIRST AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

It is recommended to avoid environmental spillage of both the product and its container.

6.3 Methods and material for containment and cleaning up:

It is recommended:



UZIN F-85 - Adhesive for printing benches

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| Identification | Occupational exposure limits | | |
|--|------------------------------|---------|-----------------------|
| | IOELV (8h) | 50 ppm | 192 mg/m ³ |
| Toluene ⁽¹⁾ CAS: 108-88-3 EC: 203-625-9 | IOELV (STEL) | 100 ppm | 384 mg/m ³ |
| m-xylene ⁽¹⁾ CAS: 108-38-3 EC: 203-576-3 | IOELV (8h) | 50 ppm | 221 mg/m ³ |
| | IOELV (STEL) | 100 ppm | 442 mg/m ³ |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | IOELV (8h) | 50 ppm | 241 mg/m ³ |
| | IOELV (STEL) | 150 ppm | 723 mg/m ³ |

⁽¹⁾ Skin

- CONTINUED ON NEXT PAGE -



UZIN F-85 - Adhesive for printing benches

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

DNEL (Workers):

| Identification | | Short exposure | | Long exposure | |
|---|------------|-----------------------|-----------------------|-----------------------|-----------------------|
| | | Systemic | Local | Systemic | Local |
| Toluene CAS: 108-88-3 EC: 203-625-9 | Oral | Not relevant | Not relevant | Not relevant | Not relevant |
| | Dermal | Not relevant | Not relevant | 384 mg/kg | Not relevant |
| | Inhalation | 384 mg/m ³ | 384 mg/m ³ | 192 mg/m ³ | 192 mg/m ³ |
| m-xylene CAS: 108-38-3 EC: 203-576-3 | Oral | Not relevant | Not relevant | Not relevant | Not relevant |
| | Dermal | Not relevant | Not relevant | 212 mg/kg | Not relevant |
| | Inhalation | 442 mg/m ³ | 442 mg/m ³ | 221 mg/m ³ | 221 mg/m ³ |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | Oral | Not relevant | Not relevant | Not relevant | Not relevant |
| | Dermal | 11 mg/kg | Not relevant | 11 mg/kg | Not relevant |
| | Inhalation | 600 mg/m ³ | 600 mg/m ³ | 300 mg/m ³ | 300 mg/m ³ |

DNEL (General population):

| Identification | | Short exposure | | Long exposure | |
|---|------------|-----------------------|-----------------------|------------------------|------------------------|
| | | Systemic | Local | Systemic | Local |
| Toluene CAS: 108-88-3 EC: 203-625-9 | Oral | Not relevant | Not relevant | 8,13 mg/kg | Not relevant |
| | Dermal | Not relevant | Not relevant | 226 mg/kg | Not relevant |
| | Inhalation | 226 mg/m ³ | 226 mg/m ³ | 56,5 mg/m ³ | 56,5 mg/m ³ |
| m-xylene CAS: 108-38-3 EC: 203-576-3 | Oral | Not relevant | Not relevant | 2,5 mg/kg | Not relevant |
| | Dermal | Not relevant | Not relevant | 125 mg/kg | Not relevant |
| | Inhalation | 260 mg/m ³ | 260 mg/m ³ | 65,3 mg/m ³ | 65,3 mg/m ³ |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | Oral | 2 mg/kg | Not relevant | 2 mg/kg | Not relevant |
| | Dermal | 6 mg/kg | Not relevant | 6 mg/kg | Not relevant |
| | Inhalation | 300 mg/m ³ | 300 mg/m ³ | 35,7 mg/m ³ | 35,7 mg/m ³ |

PNEC:

| Identification | | | | | |
|---|--------------|--------------|-------------------------|-------------|--|
| Toluene CAS: 108-88-3 EC: 203-625-9 | STP | 13,61 mg/L | Fresh water | 0,68 mg/L | |
| | Soil | 2,89 mg/kg | Marine water | 0,68 mg/L | |
| | Intermittent | 0,68 mg/L | Sediment (Fresh water) | 16,39 mg/kg | |
| | Oral | Not relevant | Sediment (Marine water) | 16,39 mg/kg | |
| m-xylene CAS: 108-38-3 EC: 203-576-3 | STP | 1,6 mg/L | Fresh water | 0,044 mg/L | |
| | Soil | 0,852 mg/kg | Marine water | 0,004 mg/L | |
| | Intermittent | 0,01 mg/L | Sediment (Fresh water) | 2,52 mg/kg | |
| | Oral | Not relevant | Sediment (Marine water) | 0,252 mg/kg | |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | STP | 35,6 mg/L | Fresh water | 0,18 mg/L | |
| | Soil | 0,09 mg/kg | Marine water | 0,018 mg/L | |
| | Intermittent | 0,36 mg/L | Sediment (Fresh water) | 0,981 mg/kg | |
| | Oral | Not relevant | Sediment (Marine water) | 0,098 mg/kg | |

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|-----------|--|-----------|---------------------|--|
| | Filter mask for gases and vapours (Filter type: A) | | EN 405:2002+A1:2010 | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |



C.- Specific protection for the hands

- CONTINUED ON NEXT PAGE -





UZIN F-85 - Adhesive for printing benches

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)


| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---|---|-------------------|--|
|  Mandatory hand protection | Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.11 mm) |  | EN ISO 21420:2020 | Replace the gloves at any sign of deterioration. |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection



| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---|---|---------------------------------|---|
|  Mandatory face protection | Panoramic glasses against splash/projections. |  | EN 166:2002 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|-----------|----------------------|--|-------------------|---|
| | Work clothing |  | | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994. |
| | Anti-slip work shoes |  | EN ISO 20347:2022 | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2022 y EN 13832-1:2019 |

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

| Emergency measure | Standards | Emergency measure | Standards |
|---|---|--|--|
|  Emergency shower | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 |  Eyewash stations | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

| | |
|---------------------------|-------------------------------------|
| V.O.C. (Supply): | 2,87 % weight |
| V.O.C. density at 20 °C: | 27,94 kg/m ³ (27,94 g/L) |
| Average carbon number: | 6,89 |
| Average molecular weight: | 93,73 g/mol |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

| | |
|--------------------------|---|
| Physical state at 20 °C: | Liquid |
| Appearance: | Cream |
| Colour: |  Cream |

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



UZIN F-85 - Adhesive for printing benches

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

| | |
|--|--------------------------|
| Odour: | Soft |
| Odour threshold: | Not relevant * |
| Volatility: | |
| Boiling point at atmospheric pressure: | 82 - 251 °C |
| Vapour pressure at 20 °C: | 2353 Pa |
| Vapour pressure at 50 °C: | 12363,88 Pa (12,36 kPa) |
| Evaporation rate at 20 °C: | Not relevant * |
| Product description: | |
| Density at 20 °C: | 974,7 kg/m ³ |
| Relative density at 20 °C: | 0,975 |
| Dynamic viscosity at 20 °C: | Not relevant * |
| Kinematic viscosity at 20 °C: | Not relevant * |
| Kinematic viscosity at 40 °C: | >20,5 mm ² /s |
| Concentration: | Not relevant * |
| pH: | Not relevant * |
| Vapour density at 20 °C: | Not relevant * |
| Partition coefficient n-octanol/water 20 °C: | Not relevant * |
| Solubility in water at 20 °C: | Not relevant * |
| Solubility properties: | Not relevant * |
| Decomposition temperature: | Not relevant * |
| Melting point/freezing point: | Not relevant * |
| Flammability: | |
| Flash Point: | Non Flammable (>60 °C) |
| Flammability (solid, gas): | Not relevant * |
| Autoignition temperature: | 393 °C |
| Lower flammability limit: | Not relevant * |
| Upper flammability limit: | Not relevant * |
| Particle characteristics: | |
| Median equivalent diameter: | Not relevant * |

9.2 Other information:

Information with regard to physical hazard classes:

| | |
|--|----------------|
| Explosive properties: | Not relevant * |
| Oxidising properties: | Not relevant * |
| Corrosive to metals: | Not relevant * |
| Heat of combustion: | Not relevant * |
| Aerosols-total percentage (by mass) of flammable components: | Not relevant * |

Other safety characteristics:

| | |
|---------------------------|----------------|
| Surface tension at 20 °C: | Not relevant * |
| Refraction index: | Not relevant * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

- CONTINUED ON NEXT PAGE -



UZIN F-85 - Adhesive for printing benches

SECTION 10: STABILITY AND REACTIVITY (continued)

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|------------|----------------|
| Not applicable | Not applicable | Precaution | Precaution | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: m-xylene (3); Toluene (3); propan-2-ol (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

** Changes with regards to the previous version



UZIN F-85 - Adhesive for printing benches

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|--|------------------------|-----------------|--------|
| | Route | Value | |
| Toluene CAS: 108-88-3 EC: 203-625-9 | LD50 oral | 5580 mg/kg | Rat |
| | LD50 dermal | 12124 mg/kg | Rat |
| | LC50 inhalation vapour | 28,1 mg/L (4 h) | Rat |
| Rosin CAS: 8050-09-7 EC: 232-475-7 | LD50 oral | 4100 mg/kg | Rat |
| | LD50 dermal | >2000 mg/kg | |
| | LC50 inhalation dust | >5 mg/L | |
| m-xylene CAS: 108-38-3 EC: 203-576-3 | LD50 oral | 1590 mg/kg | Mouse |
| | LD50 dermal | 1100 mg/kg | |
| | LC50 inhalation vapour | 11 mg/L | |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | LD50 oral | 12789 mg/kg | Rat |
| | LD50 dermal | 14112 mg/kg | Rabbit |
| | LC50 inhalation vapour | 23,4 mg/L (4 h) | Rat |
| Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Not relevant | LD50 oral | 64 mg/kg | Rat |
| | LD50 dermal | 87,12 mg/kg | Rabbit |
| | LC50 inhalation vapour | 0,5 mg/L | |

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

** Changes with regards to the previous version

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Acute toxicity:

| Identification | Concentration | | Species | Genus |
|--|---------------|-----------------|---------------------------|------------|
| | Route | Value | | |
| Rosin CAS: 8050-09-7 EC: 232-475-7 | LC50 | 150 mg/L (96 h) | Brachydanio rerio | Fish |
| | EC50 | 238 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 | 185 mg/L (72 h) | Selenastrum capricornutum | Algae |

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



UZIN F-85 - Adhesive for printing benches

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

| Identification | Concentration | Species | Genus | |
|--|---------------|---------------------------|-------------------------|------------|
| Toluene CAS: 108-88-3 EC: 203-625-9 | LC50 | 5,5 mg/L (96 h) | Oncorhynchus kisutch | Fish |
| | EC50 | 3,78 mg/L (48 h) | Ceriodaphnia dubia | Crustacean |
| | EC50 | Not relevant | | |
| m-xylene CAS: 108-38-3 EC: 203-576-3 | LC50 | 16 mg/L (96 h) | Carassius auratus | Fish |
| | EC50 | 9,56 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 | Not relevant | | |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | LC50 | Not relevant | | |
| | EC50 | Not relevant | | |
| | EC50 | 675 mg/L (72 h) | Scenedesmus subspicatus | Algae |
| Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Not relevant | LC50 | >0.001 - 0.01 mg/L (96 h) | | Fish |
| | EC50 | >0.001 - 0.01 mg/L (48 h) | | Crustacean |
| | EC50 | >0.001 - 0.01 mg/L (72 h) | | Algae |

Chronic toxicity:

| Identification | Concentration | Species | Genus | |
|---|---------------|--------------------|---------------|------------|
| m-xylene CAS: 108-38-3 EC: 203-576-3 | NOEC | 0,714 mg/L | Danio rerio | Fish |
| | NOEC | 1,57 mg/L | Daphnia magna | Crustacean |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | NOEC | Not relevant | | |
| | NOEC | 23,2 mg/L | Daphnia magna | Crustacean |
| Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Not relevant | NOEC | >0.001 - 0.01 mg/L | | Fish |
| | NOEC | >0.001 - 0.01 mg/L | | Crustacean |

12.2 Persistence and degradability:

Substance-specific information:

| Identification | Degradability | | Biodegradability | |
|---|---------------|-------------------------|------------------|--------------|
| | | | | |
| Rosin CAS: 8050-09-7 EC: 232-475-7 | BOD5 | Not relevant | Concentration | Not relevant |
| | COD | Not relevant | Period | 28 days |
| | BOD5/COD | Not relevant | % Biodegradable | 32 % |
| Toluene CAS: 108-88-3 EC: 203-625-9 | BOD5 | 2,5 g O ₂ /g | Concentration | 100 mg/L |
| | COD | Not relevant | Period | 14 days |
| | BOD5/COD | Not relevant | % Biodegradable | 100 % |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | BOD5 | Not relevant | Concentration | Not relevant |
| | COD | Not relevant | Period | 5 days |
| | BOD5/COD | Not relevant | % Biodegradable | 84 % |

12.3 Bioaccumulative potential:

Substance-specific information:

| Identification | Bioaccumulation potential | |
|---|---------------------------|----------|
| Toluene CAS: 108-88-3 EC: 203-625-9 | BCF | 90 |
| | Pow Log | 2.73 |
| | Potential | Moderate |
| m-xylene CAS: 108-38-3 EC: 203-576-3 | BCF | 15 |
| | Pow Log | 3.2 |
| | Potential | Low |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | BCF | 4 |
| | Pow Log | 1.78 |
| | Potential | Low |

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|---|-----------------------|----------------------|------------|------------------------------|
| Toluene CAS: 108-88-3 EC: 203-625-9 | Koc | 178 | Henry | 672,8 Pa·m ³ /mol |
| | Conclusion | Moderate | Dry soil | Yes |
| | Surface tension | 2,793E-2 N/m (25 °C) | Moist soil | Yes |

** Changes with regards to the previous version

UZIN F-85 - Adhesive for printing benches



SECTION 12: ECOLOGICAL INFORMATION ** (continued)

| Identification | Absorption/desorption | | Volatility | |
|-----------------|-----------------------|----------------------|------------|-------------------------------|
| m-xylene | Koc | 182 | Henry | 790,34 Pa·m ³ /mol |
| CAS: 108-38-3 | Conclusion | Moderate | Dry soil | Yes |
| EC: 203-576-3 | Surface tension | 2,826E-2 N/m (25 °C) | Moist soil | Yes |
| N-butyl acetate | Koc | Not relevant | Henry | Not relevant |
| CAS: 123-86-4 | Conclusion | Not relevant | Dry soil | Not relevant |
| EC: 204-658-1 | Surface tension | 2,478E-2 N/m (25 °C) | Moist soil | Not relevant |

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|----------|---|--|
| 08 04 10 | waste adhesives and sealants other than those mentioned in 08 04 09 | Non-hazardous |

Type of waste (Regulation (EU) No 1357/2014):

Not relevant

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1).
- Article 95, REGULATION (EU) No 528/2012: *Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9) - PT: (2,4,6,11,12,13)*
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Not relevant

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

- CONTINUED ON NEXT PAGE -

UZIN F-85 - Adhesive for printing benches



SECTION 15: REGULATORY INFORMATION (continued)

Contains more than 0.1 % of Toluene by weight. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances
N-butyl acetate (123-86-4)
- Removed substances
Butanone (78-93-3)

Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled.
- Acute Tox. 3: H301 - Toxic if swallowed.
- Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.
- Aquatic Acute 1: H400 - Very toxic to aquatic life.
- Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
- Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
- Eye Dam. 1: H318 - Causes serious eye damage.
- Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
- Flam. Liq. 3: H226 - Flammable liquid and vapour.
- Repr. 2: H361d - Suspected of damaging the unborn child.
- Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.
- Skin Irrit. 2: H315 - Causes skin irritation.
- Skin Sens. 1: H317 - May cause an allergic skin reaction.
- Skin Sens. 1A: H317 - May cause an allergic skin reaction.
- STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
- STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Skin Sens. 1: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

- <http://echa.europa.eu>
- <http://eur-lex.europa.eu>

Abbreviations and acronyms:

- CONTINUED ON NEXT PAGE -

UZIN F-85 - Adhesive for printing benches



SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -