

UZIN QUARTZ SAND

Mineral sand in several grain sizes till diameters from 75 Mesh up to 1.2mm

Applications:

Fire-dried quartz sand with grain-size from 75 Mesh till 1.2mm as a filler and for surface gritting. Broadcasting over epoxy products gives a secure and strong bond for subsequent coats.

- ▶ For filling and thickening pouring- and bonding-resins to give a homogeneous mortar
- ▶ For all reaction resin primers, e.g. UZIN PE 460, UZIN PE 480, UZIN PE 414 Turbo.
- ▶ For all crack-repair-, pouring- and bonding-resins, e.g. UZIN KR 416, UZIN KR 419 and UZIN KR 521
- ▶ As an aggregate for levelling compounds, that reduces stresses in levelling compounds and mortars; therefore increases reliability
- ▶ For all UZIN cement levelling compounds
- ▶ For aggregating UZIN levelling compounds at greater thicknesses
- ▶ For producing repair- and filling- mortars
- ▶ Interior and exterior use

Properties:

- ▶ Produces a gritted surface
- ▶ Fills and adjusts consistency
- ▶ Interior and exterior use

Technical data:

Packaging:	Paper bag
Sizes:	25 kg
Diameters:	75 Mesh, 0.1-0.3mm, 0.3-1.2mm
Storage:	min 12 months
Color:	beige

UZIN QUARTZ SAND
