

Point-to-point adhesive for paper with paper

UZIN D-300

Water dispersion adhesive for bonding paper with paper

Applications:

Economical industrial adhesive for strong but flexible paper-to-point paper bonding in point-to-point applications. Suitable for toilets and kitchen rolls, but also for industrial rolls of paper. It can be diluted with water up to 50-80 w.w.%.

Suitable for / on:

- ▶ Every paper type with or without printing
- ▶ Several types of cartons

Product properties / advantages:

Aqueous dispersion of a polyvinyl alcohol blends having high content of active solids. It dries quickly and develops maximum adhesion at early stages of drying, and once dried, it allows easy release of the paper without tearing or cracking. Suitable for machines with low to high-speed applications.

- ▶ **Economic**
- ▶ Easy spreadable
- ▶ Does not tear the paper
- ▶ In accordance with the Greek Code of Food and Beverages (KTP)

Technical Data:

Packaging:	PE container
Sizing:	30kg
Hazard:	-
Active solids:	32.5±1.5%
Color:	Milky/Transparent
Specific Gravity:	1,06kg/l
Application Temperature:	min 10°C (ASTM 2354)
Consumption:	Depends on application method
Viscosity:	1.950 - 2.750 mPas
Mean Particle Diameter:	Approx. 0,2 µm
pH:	6.0 - 6.5
FDA approval:	-
Storage:	Min. 6 months at cold and dry place ~20°C
Cleaning:	Wet film: cold water Dry film: hot water and/or detergent Stains/Spillages: UZIN OFFSET 395

* At 20 °C and R.H.65%.

UZIN D-300

Substrate preparation:

The bonding surfaces must be dry, clean and free from dust and other substances that could impair adhesion. Study carefully technical data and safety data sheets of UZIN Hellas products.

Application:

1. Place the container of adhesive indoors and let it be acclimatized, for 1-2 hours.
2. Ambient temperature and humidity must be within permissible limits. Ideal temperature conditions of application ranging from 18°C to 25°C. Do not apply adhesive at temperatures below 5°C and relative humidity greater than 60%.
3. Stir well the adhesive prior to application in order to homogenize well.
4. Keep always clean of the feeder bowl.
5. *Any dilution of the adhesive results in physical changes of the adhesion behavior: drying time, final adhesion strength, viscosity etc.* Even though in case of dilution: use clean water to a maximum percentage of 10% w/w. Always use a different clean container for the dilution and never use the initial adhesive container.

Caution! Water contains microorganisms, thus in a long stay in the container they are incubated and affecting biologically the adhesive, resulting in mold, or other unpleasant odors.

6. Always close tightly lids of the containers in order to prevent moisture loss and infections.
7. Clean tools and residues while still fresh. After hardening, residues could be removed by special solvent UZIN OFFSET 395.

Consumption:

Consumption estimation
60-90 gr/m ²
Depending on each substrate absorption

Important Notes:

- ▶ Shelf life minimum 6 months when stored in a cool dry place in original packaging. Protect from frost and heat. Opened containers must be used quickly.
- ▶ Always carry out preliminary tests with all materials together, due to seldom discoloration phenomena of adhesion application onto unstable ink/varnish substrates.

Protection of the workplace and the environment:

Solvent-free. The use of skin protection lotion is always recommended. Store out of reach from children. In the event of contact with the eyes or skin, rinse thoroughly and immediately with water. Information for persons with allergies is available at +30 210 7793777 (Greece).

Disposal:

Collect product residues wherever possible and reuse. Do not allow the sewer system, bodies of water or the soil to enter. Plastic containers emptied or scraped clean and no longer dripping from any residues can be recycled. Containers with liquid residues as well as collected liquid product residues are special waste. Containers with cured residues are construction / domestic waste.