

Acrylic coating for indoor and outdoor areas applications

UZIN DIAS

Acrylic water-based architectural color paint for indoor and outdoor areas

Description:

Acrylic water-dispersion architectural color paint. Coats and protects mineral surfaces. Easy application and coverage. Washable. Indoor and outdoor applications. Dries and could be repainted fast. It is ideal for any new or old painted exterior surface of plaster, concrete and/or cement boards. Also suitable for interior surfaces such as children's rooms, or areas with heavy pollution, e.g., nicotine, tobacco. Combines superior whiteness, high coverage, easy application with excellent workability, without roll marks and splicing.

Suitable for use on:

- ▶ Absorbent substrates like cement screeds, calcium sulphate screeds and concrete.
- ▶ Calcium/cement plasters
- ▶ Gypsum plates / Ytong
- ▶ Ceilings and walls in domestic and commercial areas, stairwells, warehouses, and general areas, which require great resistance to washing and are subjected on adverse weather conditions.

Product properties / advantages:

Acrylic water-soluble architectural color paint for interior and exterior walls and ceilings. It has great coverage and performance. Intense whiteness and excellent adhesion to all types of mineral substrates. It is not dangerous for human health and the environment.

Composition: Modified copolymer resins with inorganic fillers and suitable auxiliaries.

- ▶ Excellent whiteness
- ▶ Maximum coverage
- ▶ Easy and fast application
- ▶ Odorless without solvents
- ▶ Low emissions

Technical Data:

Package:	PE containers
Sizes:	15 kg, 5 kg and 1 kg
Storage:	minimum 12 months
Color:	White
Consumption:	80 - 150 g/m ²
Min application temperature:	10 °C
Ideal working temperatures:	15 - 25°C (substrate)
Drying Time:	30 - 60 minutes*
Repaint Time:	After 4 hours*

* At 20 °C and 65 % R.H. See also "Consumption Table".

Substrate preparation:

The substrate must be sound, load bearing, dry, free from cracks, clean and free from materials (dirt, oil, grease), that would impair adhesion. Uneven or areas with stagnating waters must be abraded and vacuumed off or be repaired first with the recommended UZIN mortar before applying DIAS.

Test the substrate in accordance with applicable standards and bulletins and report any deficiencies.

Any adhesion-reducing or unstable layers e.g., release agents, loose adhesives, compounds, covering or paint residues etc. must be removed, e.g., by brushing, abrading, grinding or shot-blasting. Thoroughly vacuum off loose material and dust. Allow any primers that are applied to dry completely.

Refer to the product data sheets for other products used.

Application:

1. Allow the container to reach room temperature before use and shake well, before the use and then empty content into a clean, oval bucket.
2. Prime newly surfaces with UZIN PE-421 or UZIN SB-500. Old painted surfaces could be primed with water diluted UZIN DIAS in a ratio 10-15% w/w.
3. Apply a uniform layer using a roller, brush, and air pistol (15-20% w/w water dilution).
4. Drying: Allow any layers that are applied to dry completely to get a uniform film. Normal time for drying is 1-2 hours for gypsum and plasters, and 2-4 hours for absorbent surfaces like cement screed and concrete. Drying time always depends on relative temperature and humidity. Best apply 2 successive layers if required.
5. Clean tools with water immediately after use.

Consumption data:

Substrate	Consumption	Drying
Cement screeds, concrete	80 – 150 g/m ²	Approx. 30 minutes*
Calcium sulphate screeds, gypsum, plasters	80 – 120 g/m ²	Approx. 60 minutes*
Non-absorbent surfaces	80 – 100 g/m ²	Approx. 90 minutes*

* At 20°C and 65% R.H.

Important notes:

- ▶ Shelf-life min. 12 months in original packaging when stored in moderately cool conditions. Re-seal opened containers tightly and use contents as quickly as possible. Allow product to reach room temperature before processing.
- ▶ Optimum working at 15 - 25 °C, substrate temperature over 15°C and relative humidity below 65 %. Mind dewpoint to avoid failures, due to water vapor condensation. Low temperatures and high humidity will delay whilst high temperatures and low humidity will accelerate the drying time.
- ▶ Do not use on chipboard panels, OSB panels or other wood-based substrates. In such cases, use a suitable primer from the current UZIN product range.
- ▶ Observe generally acknowledged industry and technology best practice, plus the respective applicable national standards. (e.g., EN, DIN).

Protection of the workplace and the environment:

Very low emissions- To the best of current knowledge, does not emit any relevant emissions of formaldehyde, harmful substances, or other volatile organic compounds (VOCs) based on the Directive 2004/42/CE (Annex II, Table A). The maximum allowable VOC content for the product subcategory, type of water-soluble product is 30g / l (2010). The product contains <30g/lt VOC. Odorless as well as ecologically and physiologically harmless when fully dried. **For allergy information, call the poison control center +30 210 7793777 (Greece).**

Disposal:

Collect and reuse product residues wherever possible. Do not dispose of into the sewer system, open water, or the soil. Empty, plastic containers (scraped clean and drip-free) can be recycled. Containers with liquid residues are classified as special waste, as are collected liquid product residues. Containers with residues that have dried solid are classified as construction / household waste.