

UZIN NITROU

Organic solvent mixture for surface cleaning and color paint dilution

Applications:

UZIN NITROU is a mixture of drastic but no dangerous organix solvents, that removes color paints and varnishes from various surfaces e.g. wood, metal, ceramic etc. It does not corrode nor discolorate the applied surfaces.

Recommended product for:

- ▶ Remove of paints and varnishes made from alkyd, epoxy, or polyurethane resins.
- ▶ Cleaning tools and accessories from residues of adhesives, paints and enamel colors and other products that cannot be cleaned with water.

Product benefits / features:

Mixture of active organic solvents for color paints and varnishes removal.

- ▶ Deep stripping
- ▶ Wide range of applications
- ▶ Does not cause corrosion.
- ▶ Does not contain trichlorethylene.

Ask and study carefully Safety Data Sheet of the product.

Technical Data:

| | |
|--------------------|---------------------------------------|
| Package: | Tin cans 1kg,5kg, 19kg & barrel 180Kg |
| Storage: | minimum 6 months |
| Color: | Transparent |
| Consumption: | Depends on the application |
| Density: | 840,72g/lt |
| Dynamic viscosity: | 0,515 cP (20°C) |
| VOC: | 840,72g/lt |
| Vapor pressure: | 53,16 mm Hg (20°C) |
| Boiling point: | 96,33°C |

* At 20°C and 65% R.H.

Important notes:

- ▶ Shelf life minimum 6 months in original packaging when stored in cool, dry conditions. Carefully and tightly seal containers and use the contents as quickly as possible.
- ▶ Optimum working conditions are 5-30°C.

Protection of the workplace and the environment:

High solvent content. Highly flammable. Irritant. Avoid skin contact with liquid products. Solvents in this product may form an explosive air-vapor-mixture. Therefore, provide good ventilation during and after use. No smoking, no open flames. Do not inhale vapors. Switch off all electric devices like door-bells, refrigerators, electric stoves, etc. Use barrier cream and protective gloves. Observe safety information on product label as well as safety data sheet.

Information for persons with allergies is available at Poison Center +30 210 7793777 (Greece).

Disposal:

Collect product residues wherever possible and reuse. Do not allow the sewer system, bodies of water or the soil to enter. Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustibile absorbents. Empty metal cans could be reused.

UZIN Hellas Polychimiki G. Matziaris S.A. operates a quality assurance system which conforms to the EN ISO 9001/2015 standard. This has been certified by ESYP Greece and TÜV Germany. Accordingly, all products and services meet the specifications laid down in this system. As individual circumstances and working practices are unknown, UZIN Hellas accepts no liability for any damage resulting from the use of any of its products. The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. The publication of this Product Data Sheet invalidates all previous Product Information 18/03/2025.

