

TECHNICAL DATA SHEET

Hot melt adhesive



STICKS 111

Hotmelt adhesive for various applications

Applications:

Hot melt adhesive for papers, cartons, packaging and bookbinding adhesions. It can be applied by spray or cylinder at 150 to 170°C.

Recommended product for:

- ▶ All types of porous materials

Technical Data:

Package:	Plastic sacks 25kg
Storage:	minimum 12 months
Color:	Pale yellow
Form:	Perles
Consumption:	Depends on the application
Brookfield viscosity (s27, 20rpm):	3000-4000 mPas at 150°C 2400-3500 mPas at 160°C
Softening point (ASTM D 17):	70-76°C
Setting time:	immediate
Working temperatures:	150-170°C

* At 20°C and 65% R.H.

Protection of the workplace and the environment:

The products in their original packing, when stored in temperatures above 30°C. can block and stick together. Do not keep them at high temperature for several hours, otherwise oxidations and toxic gases can be generated. In case of bad ventilation use of respiratory mask. Do not eat while using the product. Wash your hands at every break and at the end of the working day. Observe safety information on product label as well as safety data sheet **Information for persons with allergies is available at +30 210 7793777 (Greece).**

Disposal:

Collect product residues wherever possible and reuse. Do not allow to enter the sewer system, bodies of water or the soil. Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Empty metal cans could be reused.

UZIN Hellas Polychimiki G. Matziaris S.A. operates a quality assurance system which conforms to the EN ISO 9001/2008 standard. This has been certified by ESYS Greece and TÜV Germany. Accordingly, all products and services meet the specifications laid down in this system. As individual circumstances and working practices are unknown, UZIN Hellas accepts no liability for any damage resulting from the use of any of its products. The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. The publication of this Product Data Sheet invalidates all previous Product Information 21/11/2022

